

Floor Standing							
Items				Type	HEAT AND COOL		
				MODEL	60K T3 GFAC60		
Nameplate Parameter	Rated Capacity	Cooling		W	16000		
		Heating		W	17000		
	Rated Power	Cooling		W	6900		
		Heating		W	7000		
	Rated Running Current	Cooling		A	5050		
		Heating		A	8.6		
	Electricheating power Power			W	/		
	Max. Input Power			W	8050		
	Max. Input Current			A	13.1		
	EER Cooling			W/W	2.45		
	COP Heating			W/W	2.43		
	Power supply source			V/Ph/Hz	380~415V/50Hz		
	Refrigerant				R22		
	Refrigerant Charged			g	3900		
	Max. Discharge Pressure			Mpa	2.8		
	Max. Suction Pressure			Mpa	0.8		
	Indoor unit configuration	evaporator	Multi-bend			1	
Rows			Row	2			
Pipe			Length		mm	440	
			Diameter × Thickness		mm	Φ9.52*0.27	
		Quantity			36		
Fan		Material			AS		
		Diameter × Length		mm	φ397*180.3		
			Model		Pcs	YDK120-8B	
			Motor speed (H/M/L)		rpm	470±25 420±25 380±30	
			Rated Output Power		W	120	
Air circulation (H/M/L)				m³/h	2000		
		Dimension	Net Dimension		mm	1910*560*360	
			Packing Dimension		mm	2020*680*510	
Outdoor unit configuration		Connect pipe		Liquid tube Diameter × Thickness		mm	φ9.52×0.6
				Gas tube Diameter × Thickness		mm	φ19.05×1.0
				Compressor Model			
		Compressor Parameter	type				Scroll
	Brand				SANYO		
	Capacity		W	17300			
	Input		W	5200			
	Rated		Rate	Rated current(RLA)	A	7.6	
	Capacitor		Capa	Capacitor	uF	/	
	Refrigerant		Refri	Refrigerant oil	ml	1700	
	Fan	Fan	Vane Number			4	
			Blade Material			AS	
			Diameter		mm	Φ453	
		Fan motor	Model			YDK68-6-358(L/S)	
			Capacitor		μF	3	
			Motor speed (H/M/L)		rpm	860±30	
	Condenser	Rated Output Power		W	68		
		Rows			Row	2	
			tube pitch×row pitch			25.4*22	
		Tube	Material			Inner-grooved copper	
			Length		mm	780	
			Diameter × Thickness		mm	Φ9.52*0.27	
			Quantity			48	
	Dimension	Net Dimension		mm	1255*340*945		
		Packing Dimension		mm	1300*430*1085		
	Indoor panel length				mm	1910	
	outdoor unit size					1255*340*945	